



গণপ্রজাতন্ত্রী বাংলাদেশ সরকার

সরঞ্জাম নিয়ন্ত্রক, পশ্চিম এর কার্যালয়

বাংলাদেশ রেলওয়ে

রাজশাহী।

ফোনঃ +৮৮০৭২১-৭৬১৯৫৫, ইমেইল : cosw@railway.gov.bd.

নং-সিওএস/ই-জিপি/২০২১-০৯

তারিখঃ ২১/১০/২০২১ ইং

ই-জিপি টেন্ডার নোটিশ

সরঞ্জাম নিয়ন্ত্রক, পশ্চিম, রাজশাহী কর্তৃক National Electronic Government Procurement Portal (<http://www.eprocure.gov>).

এ নিম্নবর্ণিত দরপত্র আহ্বান করা হয়েছে।

SL No	ID, Reference No./Tender/ Proposal Status	Procurement Nature, Title	Ministry, Division, Organization, PE	Type, Method	Publishing & Closing Date (Amendment)
1.	621697, e- Tender/STR/P2/HD/2021/32/ REQ	1. Magnetic contactor, Coil voltage-77-143 VDC, Power contact composition-3 No, power poles continuous current rating-17 Amps, operational voltage- (main circuit & auxiliary circuit) - 690 VAC, 1th open contact-30 Amps, Auxiliary contact composition-1NC, Rated operational voltage-690 VAC 2. Magnetic contactor, Coil voltage-77-143 VDC, Power contact composition-3 No, power poles continuous current rating-37 Amps, operational voltage- (main circuit & auxiliary circuit) - 690 VAC 3. Mini Contactor, Relay, Coil voltage-220-230 VAC, 50/60HZ, Pole contact composition-3No+INC, Rated operational voltage (Ue)-690V 4. Mini Contactor, Relay, Coil voltage- 110VDC, 50/60HZ, Pole contact composition-3No+INC, Rated operational voltage (Ue)-690V, Conventional free air thermal current (Ith)-10A, Minimum Switching voltage-17V, 5. Magnetic contactor, Coil voltage-380-400 VAC, Power contact composition-4 No, power poles continuous current rating-350 Amps, operational voltage- (main circuit & auxiliary circuit) -1000 VAC, 6. Thermal Magnetic Motor protection circuit Breaker, Rated operational voltage-690VAC, Rated operational current-2.5A, Setting range-1.6-2.5A, Number of Poles-3, Contact position Indication-ON/OFF, with auxiliary contact INO+INC, For LHB AC Coaches water raising pump. 7. Magnetic contactor, Coil voltage-20-60 VDC, Number of main Contacts No-3, Rated operational voltage-690V, Conventional free-air thermal current (Ith) 100A, Terminal type screw terminals, (For LHB power car Battery Charger plant select) 8. Magnetic contactor, Coil voltage-110 AC/DC, Power contact composition-4 No, power poles continuous current rating-100 Amps, Rated operational voltage- 690 VAC, Connections terminal screw, rail mounting support, For LHB Non AC Coach	Ministry of Railways, Bangladesh Railway, Office of the controller of Stores-West, Rajshahi.	NCT, OTM	21-Oct-2021 14:30:00 , 07-Nov-2021 12:30:00
2.	621280, e- Tender/STR/P2/HD/2021/37/ REQ	1. Air Circuit Breaker, Number of poles-3, Rated operational voltage-750V, Rated operational current-800A, Volt metric release-MV, under voltage release-240 VAC, Number of auxiliary contact- 6No+6NC, of protection-DNIE, Earth fault release-30, 40, 50% CT for 240-300 Amps, Brand: L& T, Model No-CN-CS-800C, For LHB Power car. 2. Switch pressure Make Cummins, Part No-A028X493 (For LHB Power car) 3. Sender, Pressure for Lubo Oil, Make Cummins, Part No-A028X493 (For LHB Power car) 4. Solid state relay, Coil Voltage-110 VAC, ON-DELAY, Pin type- 11 pin, Relay Output DPDT, 2 change overs for switchboard installation analog adjustable with LED display, (For White Indonesian AC Coaches). 5. Auxiliary switch block, Auxiliary contact composition-2No+2NC, Operation current of the auxiliary contact-10A, Connections terminal-Screw, Model No-3RH192-IFA22 (For White Indonesian AC Coaches). 6. Auxiliary switch block, Auxiliary contact composition-2No+2NC, Operation current of the auxiliary contact-10A, Connections terminal-Screw, Model No- JRV1901-1A (For White Indonesian AC Coaches). 7. TPMCB 63 Amps, 400/4050 VAC with thermal over load protection, Breaking capacity-35KA. (For White Indonesian AC Coaches). 8. Fuel Flow Meter, Thread size: 1 Inch NPT, Measure accuracy ±1% Maximum working pressure: 20 BAR, Flow Range: 15-120 L/minimum, Single count: 0.00-99999, Total emulative count-0-99999, (For New fuel reservation tank)	Ministry of Railways, Bangladesh Railway, Office of the controller of Stores-West, Rajshahi.	NCT, OTM	21-Oct-2021 12:20:00 , 07-Nov-2021 11:00:00
3.	621459, e- Tender/STR/P2/HD/2021/33/ REQ	1. Magnetic contactor, Coil voltage- 230 VAC, Number of main Contacts No-3 No, Number of Auxiliary contacts -1 No, Rated operational voltage-690VAC, Conventional free-air thermal current (Ith) 50A, Connecting terminals main poles Flat type C/W screws and bolts. (For LHB power car Radiator fan motor) 2. Thermal Magnetic Motor protection circuit Breaker, Rated operational voltage-690VAC, Rated operational current-10A, Setting range-6-10A, Number of Poles-3, Contact position Indication-ON/OFF For LHB Power car Ventilation fan motor. 3. Thermal Magnetic Motor protection circuit Breaker, Rated operational voltage-690VAC, Rated operational current-63A, Setting range-45-63A, Number of Poles-3, Contact position Indication-ON/OFF, Auxiliary contact - INO, For LHB Power car Radiator fan motor 4. Disconnecting and Earthing Device, 750 VAC (1000V insulation), 63 Amps, 8-pole, 2-way, contact position-ON/OFF, Auxiliary contact -2NO+2NC with heavy handle and stainless steel box enclosure of dimension, part No-S63-73412-B32-L0CB, For LHB Non AC passengers Coach. 5. Magnetic contactor, Number of Poles-3, coil voltage-350-500VAC, Rated operational voltage-1000VAC, Rated operational current-1050A, Rated frequency (f)-50/60HZ, Short circuit protective devices-gG type fuse 1000A, Terminal type, Model No-AF750-30, For LHB Power car. 6. Mini contactor Relay, Coil voltage-24VDC, Minimum Switching capacity-17V, 5mA, Number of Auxiliary contact-2NO+2NC, Rated operational current-6A, Mounting type-DIN Rail, Mounting position-Any, Model No-TKC6-22Z, for LHB powercar.	Ministry of Railways, Bangladesh Railway, Office of the controller of Stores-West, Rajshahi.	NCT, OTM	21-Oct-2021 12:00:00 , 07-Nov-2021 12:00:00
4.	621407, e- Tender/STR/P2/HD/2021/36/ REQ	1. Cartridge High pressure switch, ACB contact function -SPST (NO), pressure connection size-1/4in, Pressure connection type-Flare, electrical connection-cable, length-1.5m, contact rating - 250VAC, 4A, Max working pressure-45bar/653 psig, ambient temperature-30A°/85A°, Refrigerants-R22/R407C, Resent function-Auto, wire color: Back, Model No ACB-2UA703W, For LHB AC Coach. 2. Cartridge High pressure switch, ACB contact function -SPST (NO), pressure connection size-1/4in, Pressure connection type-Flare, electrical connection-cable, length- 3m, contact rating - 250VAC, 4A, Max working pressure-45bar/633 psig, ambient temperature-30A°/85A°, Refrigerants-R22/R407C, Resent function-Auto, wire color: Back+Blue+Red, Model No ACB-2UC555W, For LHB AC Coach. 3. Pressure transmitter, AKS-3000, Model No: 060G6187, Pressure connection size-1/4", Pressure connection type-Flare, electrical connection-cable, Cable length-2m, Supply voltage max-350VDC, Supply voltage min-10VDC, output signal (mA) (Max-Min)-20mA-4mA, Max working pressure 0-40 Bar/580, 15 psig, ambient temperature-300c/85c, Refrigerants-R22/R407C, Resent function-Auto, wire color: Black common (-), Brown, Supply (+), For LHB AC Coach. 4. Pressure Transducer LP (0-10 bar), model No-UL3309722. 5. Pressure Transducer HP (0-40 bar), model No-UL3309722. 6. Siemens Air Break (Power contactor) 3TF31 (0-10A), auxiliary contacts-IE/AC-20A, coil voltage-220V	Ministry of Railways, Bangladesh Railway, Office of the controller of Stores-West, Rajshahi.	NCT, OTM	21-Oct-2021 11:00:00 , 07-Nov-2021 11:00:00
5.	621187, e- Tender/STR/P2/HD/2021/38/ REQ	1. AC Volt Meter 0-800V - (2.5"x2.5") 2. Amper Meter 0-150A - (2.5"x2.5") 3. Frequency Meter 440V, 55HZ-(2.5"x2.5") 4. Relay 11- Pins, Coil voltage 24 VDC, round type with base 5. Relay, 9-Pins, Coil voltage 24 VDC, round type with base. 6. Frequency meter vibration reed type 220 VAC (0-55 HZ) Size - (2.5"x2.5") 7. Frequency meter vibration reed (type 220 VAC (0-55 HZ) Size - (3.5"x3.5") 8. Magnetic contactor, Coil voltage-110 VAC, Power contact composition-3 No, power poles continuous current rating-9 Amps, Rated Operational voltage-400VAC, Service Power-4 Kw, Auxiliary contact composition-2NO+2NC, Operation current of the auxiliary contact-10A, Connections terminal-Screw, Rail mounting support, Model No: 3RT1023-1AFO4, (For White Indonesian AC Coaches). 9. Magnetic contactor, Coil voltage-110 VAC, Power contact composition-3 No, power poles continuous current rating-12 Amps, Rated Operational voltage-400VAC, Service Power-4 Kw, Auxiliary contact composition-2NO+2NC, Operation current of the auxiliary contact-10A, Connections terminal-Screw, Rail mounting support, Model No: 3RT1024-1AFO4, (For White Indonesian AC Coaches). 10. Control/contract relay, coil voltage-110VAC, Auxiliary contact composition-4No, Operating current of the Auxiliary contact-10A, Connections Terminal Screw, Rail mounting support, Model No- 3TH1140-1AFOO, (For White Indonesian AC Coaches). 11. Control/contractor relay, Coil voltage-110VAC, Auxiliary contact composition-4No, operating current of the Auxiliary contact-10A, Connections Terminal Screw, Rail mounting support, Model No- 3K1122-2AFOO, (For White Indonesian AC Coaches). 12. DPDT Plug in latching relay, Coil voltage-110 VAC, Switching current-5A, Electrical life-500000 cycles, Mounting type-plug in, contact configuration-DPDT, (For White Indonesian AC Coaches).	Ministry of Railways, Bangladesh Railway, Office of the controller of Stores-West, Rajshahi.	NCT, OTM	21-Oct-2021 11:00:00 , 07-Nov-2021 11:30:00

- বিঃদ্রঃ
- ১। শুধুমাত্র ই-জিপি সিস্টেমে নিবন্ধিত ও দরপত্রের Eligibility শর্তাবলী পূরণকারী সরবরাহকারীগণ দরপত্রে অংশগ্রহণ করতে পারবেন।
  - ২। নিবন্ধিত ও অগ্রহী দরদাতাগণ বিনা খরচে দরপত্র দেখতে পারবেন, তবে দরপত্রে অংশগ্রহণের জন্য দরপত্র দলিল ও দরপত্র জামানত বাবদ অর্থ নির্ধারিত ব্যাংকে জমা করতে হবে।
  - ৩। পর্যায়ক্রমে সকল দরপত্র পদ্ধতির ক্ষেত্রে ই-জিপি সিস্টেম ব্যবহার করা যাবে। তালিকাভুক্ত সকল দরদাতাগণকে অবিলম্বে ই-জিপি সিস্টেমে তথ্য National Electronic Government Procurement Portal (<http://www.eprocure.gov>)/ তে নিবন্ধিত হওয়ার জন্য অনুরোধ করা হল।

(প্রকৌশল মুহাম্মদ রাশেদুল আমিন)  
সরঞ্জাম নিয়ন্ত্রক, পশ্চিম  
বাংলাদেশ রেলওয়ে, রাজশাহী।